

MATERIAL SAFETY DATA SHEET

RAM Petrolatum Primer

PRODUCT IDENTIFICATION

MANUFACTURER'S NAME: Australasian Industrial Wrappings & Coatings P/L

REGULAR TELEPHONE NUMBER: 02 9608 8111
EMERGENCY TELEPHONE NUMBER: 0419 242 638
FACSIMILE NUMBER: 02 8783 7055

ADDRESS:
49 JEDDA ROAD, PRESTONS NSW 2170

PRODUCT NAME: RAM PETROLATUM PRIMER

• SYNONYMS:

MANUFACTURER'S CODE:
100 - - -

• USES: Corrosion Inhibitor. Primer.

HAZARD IDENTIFICTATION

NOT CLASSIFIED AS HAZARDOUS ACCORDINGING TO SAFE WORK AUSTRALIA CRITERIA.

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE.

UN.No: None allocated. **DG Class:** None allocated **Subsidiary Risk:** None allocated.

Packing Group: None allocated Hazchem Code: None allocated.

COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT	FORMULA	CAS No.	CONTENT
PETROLATUM WAX	NOT AVAILABLE	NOT AVAILABLE	>60%
FILLER	NOT AVAILABLE	NOT AVAILABLE	NOT AVAILABLE
INHIBITORS	NOT AVAILABLE	NOT AVAILABLE	NOT AVAILABLE

FIRST AID MEASURES

Eye If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing

until advised to stop by a Poison Information Centre, a doctor, or for at least 15 minutes.

Inhalation If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with

running water. Continue flushing with water until advised to stop by a poison Information

Centre pr a doctor.

Ingestion For advice contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor (at

once). If swallowed do not induce vomiting.

Advice to Doctor Treat Sympathetically.

FIRE FIGHTING MEASURES

Flammability Combustible. May evolve toxic gases (Carbon oxides, hydrocarbons) when heated to

decomposition.

Fire and Explosion Evacuate area and contact emergency services. Toxic gases may be evolved in a fire

situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use

water fog to cool intact containers and nearby storage areas.

Extinguishing Dry agent, carbon dioxide or foam. Prevent contamination of drains or waterways.

Hazchem Code None allocated.

ACCIDENTAL RELEASE MEASURES

Spillage Contact emergency services where appropriate. Use personal protective equipment. Clear

area of all unprotected personnel. Ventilate area where possible. Contain spillage, then cover/ absorb spill with non – combustible absorbent material (vermiculite, sand or similar), collect and place in suitable containers for disposal. CAUTION: Spill site may be slippery.

STORAGE AND HANDLING

Storage Store in cool, dry well ventilated area, removed from oxidising agents, acids, heat or ignition

sources and food stuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Large storage areas should have appropriate ventilation system. Store as a Class C1 Combustible Liquid (AS1940). Also store removed from aromic

solvents.

Handling Before use carefully read the product label. Use of safe work practices are recommended to

avoid eye or skin contact and inhalation. Observe good personnel hygiene. Including washing

hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

EXPOSURE CONTROLS/ PERSONAL PROTECTION

Exposure Stds

Ingredient	Reference	TWA	STEL
Paraffin wax (fume)	ASCC (AUS)	- 2mg/m3	

Biological Limits No biological limit allocated.

Engineering Controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exits, mechanical extraction ventilation is recommended. Maintain vapour levels below the recommended exposure standard.

PPE Wear splash-proof goggles and nitrile or neoprene gloves. When using large quantities or where heavy contamination is likely, wear: coneralla. Where an inhalation risk exists, wear: a Type A (Organic vapour) respiration.

PHYSICAL AND CHEMICAL PROPERTIES

Appearance Green or brown grease Solubility (water) Insoluble

Odour Slight odour Specific Gravity 1.1 (Approx)

Ph Not available % Volatiles 0%

Vapour Pressure Not available Flammability Class C2 Combustible

Vapour Density Not available **Flash Point** >180 °C

Boiling Point Not available **Upper Explosion Limit** Not available

Evaporation RateNot available

STABILITY AND REACTIVITY

Chemical Stability Stable under recommended conditions of storage.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources.

Material to avoid Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), heat

and ignition sources. Also incompatible with aromatic solvents.

Hazardous Decomposition May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.

Hazardous Reactions Polymerization is not expected to occur.

TOXICOLOGY INFORMATION

Health Hazard Summary Low toxicity. This product has the potential to cause adverse health effects with

direct eye contact, prolonged skin contact or vapour inhalation in poorly ventilated areas. Use safe work practices to avoid eye contact and vapour generation –

inhalation.

Eye Low to moderate irritant. Contact may result in irritation, lacrimation, pain and

redness.

Inhalation Low to moderate irritant. Over exposure may result in irritation of the nose and

throat, coughing, dizziness and headache.

Skin Irritant. Contact may result in drying and defatting of the skin, rash and dermatitis.

Ingestion Low toxicity. Ingestion of large quantities may result in nausea, vomiting, abdominal

pain, diarrhoea and drowsiness. Aspiration may result in chemical pneumonitis and

pulmonary oedema.

Toxicity Data No LD50 data available for this product.

ECOLOGICAL INFORMATION

Environment Limited ecotoxicity data was available for this product at the time this report was

prepared. Ensure appropriate measures are taken to prevent this product from

entering the environment.

DISPOSAL CONSIDERATIONS

Waste Disposal For small amounts absorb with sand, vermiculite or similar and dispose of to an

approved landfill site. Contact the manufacturer for additional information if larger amounts are involved. Prevent contamination of drains and waterways as aquatic

life may be threatened and environmental damage may result.

Legislation Dispose of in accordance with relevant local legislation.

TRANSPORT INOFRMATION

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE.

Shipping Name: None allocated UN No. None allocated Packing Group: None allocated

DG Class: None allocated Hazchem code: None allocated Subsidiary Risk: None allocated

REGULATORY INFOMRATION

Poison Schedule A poison schedule number has not been allocated to this product using the criteria in the standard for the uniform scheduling of drugs and poisons (SUSDP).

All chemicals listed on the Australian Inventory of Chemical Substances (AICS)

OTHER HANDLING AND STORAGE

REQUIREMENTS: Store in original packaging in a cool place away from boilers or

heaters

PREPARED BY: Roger McElhone

ADDRESS: 49 JEDDA ROAD, PRESTONS NSW 2170

DATE: 11th JUNE 2018



AUSTRALASIAN INDUSTRIAL WRAPPINGS AND COATINGS PTY LTD 49 JEDDA ROAD, PRESTONS 2170 NSW AUSTRALIA

TEL: 02 9608 8111 FAX: 02 8783 7055

EMAIL: enquiries@aiwc.com.au WEB: www.aiwc.com.au

