

Safety Data Sheet PTG-4001

Prepared in accordance with the model Work Health and Safety Regulations

Date of issue: 05/25/2015 Revision date: 01/14/2016 Version: 1.1

SECTION: 1. Product and company identification

1.1. Product identifier

Product form : Mixture
Name : PTG-4001

Formula : (0.00001 - 0.9999 %) Hydrogen Sulfide, (0.0001 - 0.0999 %) Carbon Monoxide, (0.0001 - 3.5

%) Methane, (0.0001 - 23 %) Oxygen in Nitrogen.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Calibration / Reference
Use of the substance/mixture : Industrial use. Use as directed.

1.3. Details of the supplier of the safety data sheet

Manufactured For: By:

Scientific Gas Australia Pty Ltd.

Unit 3, 1 Perry Street

Matraville NSW, 2036 - Australia

PortaGas (Praxair, Inc.)
1202 E Sam Houston Pkwy S
Pasadena, TX 77503

T PH 1300 880 531 T 281-928-6477

1.4. Emergency telephone number

Emergency number : Onsite Emergencies: 1-800-645-4633; Australian Poison Information Centre: 13 11 26;

Australian Fire Brigade: 000

CHEMTREC: USA 1-800-424-9300, International 001-703-527-3887 (Collect calls accepted,

contract 17729)

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS-AU)

Compressed gas H280 Aquatic Acute 3 H402

2.2. Label elements

GHS-AU labelling

Hazard pictograms (GHS-AU)



GHS04

Signal word (GHS-AU) : WARNING

Hazard statements (GHS-AU) : H280 - CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED

H402 - HARMFUL TO AQUATIC LIFE

Precautionary statements (GHS-AU) : P273 - Avoid release to the environment

P410+P403 - Protect from sunlight. Store in a well-ventilated place

P501 - Dispose of contents/container in accordance with container Supplier/owner instructions

CGA-PG21 - Open valve slowly

CGA-PG12 - Do not open valve until connected to equipment prepared for use CGA-PG11 - Never put cylinders into unventilated areas of passenger vehicles

CGA-PG10 - Use only with equipment rated for cylinder pressure CGA-PG06 - Close valve after each use and when empty CGA-PG05 - Use a back flow preventive device in the piping

CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F)

CGA-MP01 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get

medical advice/attention

P261 - Avoid breathing gas, vapors

EN (English - AU) SDS ID: PTG-4001 1/11



Safety Data Sheet PTG-4001

Prepared in accordance with the model Work Health and Safety Regulations Date of issue: 05/25/2015 Revision date: 01/14/2016 Version: 1.1

2.3 Other hazards

No additional information available

Unknown acute toxicity (GHS US) 2.4.

No data available

SECTION 3: Composition/Information on ingredients

Substance

Not applicable

3.2. **Mixture**

Name	Product identifier	%
Nitrogen	(CAS No) 7727-37-9	74.5002 - 100
Oxygen	(CAS No) 7782-44-7	0.0001 - 23
Methane	(CAS No) 74-82-8	0.0001 - 3.5
Hydrogen sulfide	(CAS No) 7783-06-4	0.0001 - 1
Carbon monoxide	(CAS No) 630-08-0	0.0001 - 0.0999

SECTION 4: First aid measures

Description of first aid measures

Remove to fresh air and keep at rest in a position comfortable for breathing. If not breathing, First-aid measures after inhalation

give artificial respiration. If breathing is difficult, trained personnel should give oxygen. Call a

physician.

First-aid measures after skin contact

: Adverse effects not expected from this product.

First-aid measures after eye contact

Immediately flush eyes thoroughly with water for at least 15 minutes. Hold the eyelids open and

away from the eyeballs to ensure that all surfaces are flushed thoroughly. Contact an

ophthalmologist immediately.

First-aid measures after ingestion

: Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries

: Effects are due to lack of oxygen. Moderate concentrations may cause headache, drowsiness, dizziness, excitation, excess salivation, vomiting, and unconsciousness. Prolonged exposure to low concentrations of carbon monoxide can kill. Inhalation.

Indication of any immediate medical attention and special treatment needed 4.3.

None.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

HazChem code

5.2. Special hazards arising from the substance or mixture

Fire hazard : Not flammable.

Explosion hazard Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of

burns and injuries.

: No reactivity hazard other than the effects described in sub-sections below. Reactivity

5.3. Advice for firefighters

: Evacuate all personnel from the danger area. Use self-contained breathing apparatus (SCBA) Firefighting instructions

and protective clothing. Immediately cool containers with water from maximum distance. Remove ignition sources if safe to do so. Remove containers from area of fire if safe to do so.

On-site fire brigades must comply with their provincial and local fire regulations.

Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire Special protective equipment for fire fighters

fighters.

Other information Containers are equipped with a pressure relief device. (Exceptions may exist where authorized

by DOT.).

SDS ID: PTG-4001 2/11



Safety Data Sheet PTG-4001

Prepared in accordance with the model Work Health and Safety Regulations Date of issue: 05/25/2015 Revision date: 01/14/2016 Version: 1.1

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent waste from contaminating the surrounding environment. Prevent soil and water pollution. Dispose of contents/container in accordance with local/regional/national/international regulations. Contact supplier for any special requirements.

6.3. Methods and material for containment and cleaning up

No additional information available

6.4. Reference to other sections

See also sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Wear leather safety gloves and safety shoes when handling cylinders. Protect cylinders from physical damage; do not drag, roll, slide or drop. While moving cylinder, always keep in place removable valve cover. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Never insert an object (e.g, wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Slowly open the valve. If the valve is hard to open, discontinue use and contact your supplier. Close the container valve after each use; keep closed even when empty. Never apply flame or localized heat directly to any part of the container. High temperatures may damage the container and could cause the pressure relief device to fail prematurely, venting the container contents. For other precautions in using this product, see section 16.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

Storage conditions

- : Comply with applicable regulations.
- Store in a cool, well-ventilated place. Store and use with adequate ventilation. Store only where temperature will not exceed 125°F (52°C). Firmly secure containers upright to keep them from falling or being knocked over. Install valve protection cap, if provided, firmly in place by hand. Store full and empty containers separately. Use a first-in, first-out inventory system to prevent storing full containers for long periods

OTHER PRECAUTIONS FOR HANDLING, STORAGE, AND USE: When handling product under pressure, use piping and equipment adequately designed to withstand the pressures to be encountered. Never work on a pressurized system. Use a back flow preventive device in the piping. Gases can cause rapid suffocation because of oxygen deficiency; store and use with adequate ventilation. If a leak occurs, close the container valve and blow down the system in a safe and environmentally correct manner in compliance with all international, federal/national, state/provincial, and local laws; then repair the leak. Never place a container where it may become part of an electrical circuit.

7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Hydrogen sulfide (7783-06-4)		
ACGIH	ACGIH TLV-TWA (ppm)	1 ppm
ACGIH	ACGIH TLV-STEL (ppm)	5 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	20 ppm



Safety Data Sheet PTG-4001

Prepared in accordance with the model Work Health and Safety Regulations

Date of issue: 05/25/2015 Revision date: 01/14/2016 Version: 1.1

Hydrogen sulfide (7783-06	G-4)	
AU SWA TWA PPM	TWA (ppm)	10 ppm
AU SWA TWA MGM3	TWA (mg/m³)	14 mg/m³
AU STEL PPM	STEL (ppm)	15 ppm
AU SWA STEL MGM3	STEL (mg/m³)	14 mg/m³
Carbon monoxide (630-08	-0)	1
ACGIH	ACGIH TLV-TWA (ppm)	25 ppm
ACGIH	Biological Exposure Indices (BEI)	3.5 % of hemoglobin Parameter: Carboxyhemoglobin - Medium: blood - Sampling time: end of shift (background, nonspecific) 20 ppm Parameter: Carbon monoxide - Medium: endexhaled air - Sampling time: end of shift (background, nonspecific)
USA OSHA	OSHA PEL (TWA) (mg/m³)	55 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm
AU SWA TWA PPM	TWA (ppm)	30 ppm
AU SWA TWA MGM3	TWA (mg/m³)	34 mg/m³
AU SWA STEL MGM3	STEL (mg/m³)	34 mg/m³
Oxygen (7782-44-7)	,	
ACGIH	Not established	
USA OSHA	Not established	
Nitrogen (7727-37-9)		
ACGIH	Not established	
USA OSHA	Not established	
Methane (74-82-8)		
ACGIH	Not established	
USA OSHA	Not established	

8.2. Exposure controls

Appropriate engineering controls

: Provide adequate general and local exhaust ventilation. Ensure exposure is below occupational exposure limits (where available).

Personal protective equipment

: Safety glasses. Gloves.





Eye protection

: Wear safety glasses when handling cylinders; vapor-proof goggles and a face shield during cylinder changeout or whenever contact with product is possible. Select eye protection in accordance with AS/NZS 1336 and AS/NZS 1337.

Skin and body protection

: Wear work gloves and metatarsal shoes for cylinder handling. Protective equipment where needed. Select in accordance with AS/NZS 2161, AS/NZS 2210.1, and AS/NZS 4503.

Respiratory protection

: When workplace conditions warrant respirator use, follow a respiratory protection program that meets AS/NSZ 1715, AS/NSZ 1716, ANSI Z88.2, or MSHA 30 CFR 72.710 (where applicable). Use an air-supplied or air-purifying cartridge if the action level is exceeded. Ensure that the respirator has the appropriate protection factor for the exposure level. If cartridge type respirators are used, the cartridge must be appropriate for the chemical exposure. For emergencies or instances with unknown exposure levels, use a self-contained breathing apparatus (SCBA).

Thermal hazard protection

: Wear cold insulating gloves when transfilling or breaking transfer connections.

SDS ID: PTG-4001 4/11



Safety Data Sheet PTG-4001

: No data available

Prepared in accordance with the model Work Health and Safety Regulations
Date of issue: 05/25/2015 Revision date: 01/14/2016 Version: 1.1

SECTION 9: Physical and chemical properties

9.1. lı	nformation on	basic physic	cal and chemi	cal properties

Physical state : Gas
Color : Colorless

Odor : No data available Odor threshold : No data available Not applicable. Relative evaporation rate (butyl acetate=1) : No data available Relative evaporation rate (ether=1) : Not applicable. Melting point : No data available Freezing point : No data available No data available **Boiling point** No data available Flash point : No data available Auto-ignition temperature No data available Decomposition temperature Flammability (solid, gas) : No data available Vapor pressure : Not applicable.

Relative density : No data available
Solubility : Water: No data available

Log Pow: Not applicable.Log Kow: Not applicable.Viscosity, kinematic: Not applicable.Viscosity, dynamic: Not applicable.Explosive properties: Not applicable.

Oxidizing properties : None.

Explosion limits : No data available

9.2. Other information

Relative vapor density at 20 °C

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

None.

10.5. Incompatible materials

None.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

SDS ID: PTG-4001 5/11



Safety Data Sheet PTG-4001

Prepared in accordance with the model Work Health and Safety Regulations

Date of issue: 05/25/2015 Revision date: 01/14/2016 Version: 1.1

PTG-4001	
LD50 oral rat	≈
Hydrogen sulfide (7783-06-4)	
LC50 inhalation rat (ppm)	356 ppm/4h
ATE US (gases)	356.000 ppmV/4h
Carbon monoxide (630-08-0)	
LC50 inhalation rat (ppm)	3760 ppm/1h
ATE US (gases)	1880.000 ppmV/4h

Skin corrosion/irritation : Not classified

pH: Not applicable.

Serious eye damage/irritation : Not classified

pH: Not applicable.

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
Specific target organ toxicity (single exposure) : Not classified
Specific target organ toxicity (repeated : Not classified

exposure)

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : No known ecological damage caused by this product.

Hydrogen sulfide (7783-06-4)	
LC50 fish 1	0.0448 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through])
LC50 fish 2	0.016 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])

12.2. Persistence and degradability

PTG-4001		
Persistence and degradability	No ecological damage caused by this product.	
Hydrogen sulfide (7783-06-4)		
Persistence and degradability	Not applicable for inorganic gases.	
Oxygen (7782-44-7)		
Persistence and degradability	No ecological damage caused by this product.	
Nitrogen (7727-37-9)		
Persistence and degradability	No ecological damage caused by this product.	
Methane (74-82-8)		
Persistence and degradability	The substance is biodegradable. Unlikely to persist.	

12.3. Bioaccumulative potential

PTG-4001		
Log Pow	Not applicable.	
Log Kow	Not applicable.	
Bioaccumulative potential	No ecological damage caused by this product.	
Hydrogen sulfide (7783-06-4)		
BCF fish 1	(no bioaccumulation expected)	
Log Pow	Not applicable.	
Log Kow	Not applicable.	
Bioaccumulative potential	No data available.	

SDS ID: PTG-4001 6/11



Safety Data Sheet PTG-4001

Prepared in accordance with the model Work Health and Safety Regulations Date of issue: 05/25/2015 Revision date: 01/14/2016 Version: 1.1

Carbon monoxide (630-08-0)			
Log Kow	Not applicable.		
Oxygen (7782-44-7)	Oxygen (7782-44-7)		
Log Pow	Not applicable.		
Log Kow	Not applicable.		
Bioaccumulative potential	No ecological damage caused by this product.		
Nitrogen (7727-37-9)			
Log Pow	Not applicable.		
Log Kow	Not applicable.		
Bioaccumulative potential	No ecological damage caused by this product.		
Methane (74-82-8)			
Log Pow	1.09		
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.		
12.4. Mobility in soil			

PTG-4001		
Mobility in soil	No data available.	
Hydrogen sulfide (7783-06-4)		
Mobility in soil	No data available.	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.	
Carbon monoxide (630-08-0)		
Mobility in soil	No data available.	
Oxygen (7782-44-7)		
Mobility in soil	No data available.	
Ecology - soil	No ecological damage caused by this product.	
Nitrogen (7727-37-9)		
Mobility in soil	No data available.	
Ecology - soil	No ecological damage caused by this product.	
Methane (74-82-8)		
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.	

Other adverse effects

Effect on ozone layer : None

SECTION 13: Disposal considerations

Waste treatment methods

Waste treatment methods : Do not attempt to dispose of residual or unused quantities. Return container to supplier. : Do not attempt to dispose of residual or unused quantities. Return container to supplier. Waste disposal recommendations

SECTION 14: Transport information

Transport of Australian Dangerous Goods

UN-No. (ADG) : UN1956

: COMPRESSED GAS, N.O.S. Proper Shipping Name (ADG)

Class (ADG) : 2.2 - 2.2 - Class 2.2 - Non-flammable compressed gas

Danger labels (ADG) : 2.2 - Non-flammable compressed gas



SDS ID: PTG-4001 7/11



Safety Data Sheet PTG-4001

Prepared in accordance with the model Work Health and Safety Regulations

Date of issue: 05/25/2015 Revision date: 01/14/2016 Version: 1.1

Special provision (ADG) : 274

In accordance with DOT

Transport document description : UN1956 Compressed gas, n.o.s., 2.2

UN-No.(DOT) : UN1956

Proper Shipping Name (DOT) : Compressed gas, n.o.s.

Class (DOT) : 2.2 - 2.2 - Class 2.2 - Non-flammable compressed gas

Hazard labels (DOT) : 2.2 - Non-flammable gas

DOT Symbols : G - Identifies proper shipping name (PSN) requiring the addition of technical name(s) in

parentheses following the PSN

Additional information

Emergency Response Guide (ERG) Number : 126

HazChem code : 2TE.

Other information : No supplementary information available.

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's

compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers:
- Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure cylinder valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided)

is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.

Transport by sea

UN-No. (IMDG) : 1956

Proper Shipping Name (IMDG) : COMPRESSED GAS, N.O.S.

 Class (IMDG)
 : 2 - Gases

 Limited quantities (IMDG)
 : 120ml

 EmS-No. (1)
 : F-C

 MFAG-No
 : 620

 EmS-No. (2)
 : S-V

Air transport

UN-No. (IATA) : 1956

Proper Shipping Name (IATA) : Compressed gas, n.o.s.

Class (IATA) : 2
Instruction "cargo" (ICAO) : 200
Instruction "passenger" (ICAO) : 200

Instruction "passenger" - Limited quantities

(ICAO)

: FORBIDDEN

Civil Aeronautics Law : Gases under pressure/Gases nonflammable nontoxic under pressure(Hazardous materials

notice Appended Table 1 Article 194 of the Enforcement Regulations)

SDS ID: PTG-4001 8/11



Safety Data Sheet PTG-4001

Prepared in accordance with the model Work Health and Safety Regulations
Date of issue: 05/25/2015 Revision date: 01/14/2016 Version: 1.1

SECTION 15: Regulatory information

15.1. US Federal regulations

PTG-4001

Listed on the United States SARA Section 302

Subject to reporting requirements of United States SARA Section 313

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Hydrogen sulfide (7783-06-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on the United States SARA Section 302 Subject to reporting requirements of United States SARA Section 313	
SARA Section 302 Threshold Planning Quantity (TPQ) 500 lb	
SARA Section 313 - Emission Reporting	1.0 %

15.2. International regulations

CANADA

PTG-4001

Listed on the Canadian DSL (Domestic Substances List)

Hydrogen sulfide (7783-06-4)

Listed on the Canadian DSL (Domestic Substances List)

Carbon monoxide (630-08-0)

Listed on the Canadian DSL (Domestic Substances List)

Oxygen (7782-44-7)

Listed on the Canadian DSL (Domestic Substances List)

Nitrogen (7727-37-9)

Listed on the Canadian DSL (Domestic Substances List)

Methane (74-82-8)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

Hydrogen sulfide (7783-06-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

15.2.2. National regulations

Hydrogen sulfide (7783-06-4)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the Canadian IDL (Ingredient Disclosure List)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

SDS ID: PTG-4001 9/11



Safety Data Sheet PTG-4001

Prepared in accordance with the model Work Health and Safety Regulations

Date of issue: 05/25/2015 Revision date: 01/14/2016 Version: 1.1

15.3. US State regulations PTG-4001()	
U.S California - Proposition 65 - Carcinogens List	No
U.S California - Proposition 65 - Developmental Toxicity	Yes
U.S California - Proposition 65 - Reproductive Toxicity - Female	No
U.S California - Proposition 65 - Reproductive Toxicity - Male	No

Hydrogen sulfide (7783	-06-4)			
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
Carbon monoxide (630-	08-0)	<u> </u>		
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	Yes	No	No	
Oxygen (7782-44-7)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
Nitrogen (7727-37-9)	<u> </u>			
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
Methane (74-82-8)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

Hydrogen sulfide (7783-06-4)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Carbon monoxide (630-08-0)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Oxygen (7782-44-7)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

SDS ID: PTG-4001 10/11



Safety Data Sheet PTG-4001

Prepared in accordance with the model Work Health and Safety Regulations Date of issue: 05/25/2015 Revision date: 01/14/2016 Version: 1.1

Nitrogen (7727-37-9)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Methane (74-82-8)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

SECTION 16: Other information

Other information

: When you mix two or more chemicals, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an industrial hygienist or other trained person when you evaluate the end product. Before using any plastics, confirm their compatibility with this product

Praxair asks users of this product to study this SDS and become aware of the product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this SDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information

The opinions expressed herein are those of qualified experts within Praxair, Inc. We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and the conditions of use are not within the control of Praxair, Inc, it is the user's obligation to determine the conditions of safe use of the product

Praxair SDSs are furnished on sale or delivery by Praxair or the independent distributors and suppliers who package and sell our products. To obtain current SDSs for these products, contact your Praxair sales representative, local distributor, or supplier, or download from www.praxair.com. If you have questions regarding Praxair SDSs, would like the document number and date of the latest SDS, or would like the names of the Praxair suppliers in your area, phone or write the Praxair Call Center (Phone: 1-800-PRAXAIR/1-800-772-9247; Address: Praxair Call Center, Praxair, Inc, P.O. Box 44, Tonawanda, NY 14151-0044)

PRAXAIR and the Flowing Airstream design are trademarks or registered trademarks of Praxair Technology, Inc. in the United States and/or other countries.

SDS Australia - Praxair

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.