

# Rubber Speed Hump End Cap - 50mm(H) x 200mm (W) x 320mm (L) Yellow

## Product Images





## Short Description

---

One speed hump end piece, sold individually (not as pairs). Order two of these end pieces along with [yellow speed hump sections](#) and [black speed hump sections](#) to create the desired width speed hump for your road or driveway. Size: 50mm(H) x 200mm x (W) 320mm(L)

## Description

---

- Cost effective and durable solution for control of speed
- Made from compression moulded 80% recycled rubber and 20% Virgin Rubber
- c2 x bolts & plugs included with each section and end cap
- Complies with AU Standards AS2890.1:2004 (Type 2)

### Specifications

- Fitting Holes: Middle: 2 Holes x 12mm  $\varnothing$ , End Cap: 2 Holes x 12mm  $\varnothing$
- Weight: 4kg
- Bearing Capacity : 20T
- Reflector: 4pcs x Cats-Eye hump section only
- Tensile Strength: 6.0MPA
- Elongation at break: 200%
- Hardness: 85A
- Impact elasticity: 37%
- Abrasion Performance: 0.28cm<sup>3</sup> /1.61km

### Type 2 Speed Hump:

These speed hump sections comply with Australian Standard AS2890.1:2004 Parking Facilities, and are suitable as a Type 2 road hump. This means that they meet the design criteria for height, cross section, markings and ramp angles. The hump is 50mm high which conforms to the standard specification "must be between 25mm and 75mm". The cross section is flat on top not rounded, ensuring it meets the standard. Also, the speed hump sections have the required ramp angle of 2:1, and when installed in an alternating black/yellow pattern, they provide the appropriate 250mm wide striped markings.

## Additional Information

---

CODE	SWSH5-ENDY
U.O.M	Each
Arrow Direction	No Arrow
Width	250 mm
Height	50 mm
Length	350 mm

