

Jersey Kerb Delineator - Stripe Right (single sided)

Product Images



Short Description

Jersey Kerb Delineator - Stripe Right Diagonal - Right side of road

Description

Retro reflective units (delineators) are made from 1.6mm thick aluminium panels in accordance with RMS specifications. A diagonal slash of Class 1A fluorescent reflective sheeting is attached to one side of the panel, on a black non-reflective background.

The direction of the diagonal slash is forward if it is located on the right hand side of the traffic and if the barrier is located on the left hand side of the traffic, a backward slash is used. This jersey kerb delineator is single sided.

The yellow and black jersey kerb reflectors are typically attached to concrete barriers at 20 metre spacing to provide a coherent pattern of delineation.

Features:

- 200mm high
- 150mm wide
- Class 1A reflective stripe in yellow/green on a black background
- 1.6mm thick rigid aluminium
- Pre drilled holes in the bracket - 2 x 10mm diameter
- Can be fixed using epoxy
- 75mm wide bracket feet on opposite sides of the base
- Ideal for delineation on concrete barriers, jersey kerb, Deltabloc barriers, F Type and PCBs
- Available in other styles including arrows

Additional Information

CODE	14-JKMDD-R
U.O.M	Each
Height	210 mm
Width	150 mm

