

Horizontal Safety Line 20m

Product Images



Short Description

20 metre long horizontal safety / temporary static line for roofers and height work. Complies with AS/NZS1891.2 and EN 795:1996 Class B. Rated for 2 people, ideal for usage between 3 to 20 metres.

Description

The LINQ portable anchorage lifeline is engineered for extreme workplace situations. This horizontal webbing safety lines give lateral and versatile continuous anchorage connections. Complies with AS/NZS1891.2 and EN 795:1996 Class B, the product has been developed to be durable and efficient in setup and pack down. The webbing temporary static line kit is a lightweight 20m line, complete with ratchet tensioner for quick and easy installation. It is suitable for 2 people and comes equipped with double action karabiners and a stow bag.

Features:

- Complies with AS/NZS1891.2 and EN 795:1996 Class B
- Durable and efficient in setup and pack down
- The webbing temporary static line kit is a lightweight, 20m line, complete with ratchet tensioner for quick and easy installation
- Rated for 2 people
- Kit has an easy to use ratchet tensioning device to tighten the line
- Easy installation and removal
- Ideal for usage between 3 to 20 meters
- Includes sewn on bag for easy storage and transportation
- Equipped with two double action karabiners
- provided for attachment to anchor points
- Conforms to AS/NZS1891.2
- Conforms to standard EN 795:1996
- Passed the corrosion test in accordance with ISO 9227:1990 - 24 hours

Additional Information

CODE	32-HZSL
U.O.M	Each
Brand	Linq
Length	20 m

