

---

# Precast Concrete Storm Water Risers 450 x 450 x 300 mm

## Product Images

---



## Short Description

---

NSW Precast Concrete Storm Water Risers 450 x 450 x 300 mm, manufactured and tested as per AS4671 to meet class D wheel loading. For use in New South Wales only

## Description

---

Precast concrete Pit Riser Unit - 450 x 450 x 300 mm. Jaybro manufacture a range of precast stormwater risers. Designed to offer an off the shelf solution for drainage projects.

Recommended for applications including subdivision inter allotment drainage through to commercial and industrial complexes.

The risers come in a range of standard sizes offering greater flexibility on site compared with cast insitu and custom made pits.

Manufactured and tested as per AS4671 to meet class D wheel loading.

### USES

- Residential Drainage
- Sports fields
- Commercial and Industrial Complexes

### FEATURES

- Wet cast
- Tested to Class D wheel loading
- Minimum 40mpa Concrete
- Steel reinforcement to AS4671
- Polypropylene fiber reinforcement mean strength of 650mpa
- Concrete Lifting eye's for safety

### CONCRETE RISER ACCESSORIES

Jaybro supplies a wide range of accessories to pair with our riser unites. Including pits, grates and lids. If you can't find the solution you are looking for, call 1300 885 364 now! Our drainage experts can recommend a solution to fill your need. We can source and manufacture precast concrete solutions to fill your needs.

## Additional Information

---

CODE	PR040403
U.O.M	Each
Weight	250
Dimensions	450 x 450 x 300mm
Length	450 mm
Height	450 mm
Width	300 mm

