

Precast Concrete Storm Water Risers 900 x 600 x 150 mm

Product Images



Short Description

NSW Precast Concrete Storm Water Risers $900 \times 600 \times 150$ mm, manufactured and tested as per AS4671 to meet class D wheel loading. For use in New South Wales only

Description

Precast concrete Pit Riser Unit - $900 \times 600 \times 150$ mm. Jaybro manufacture a range of precast stormwater risers. Designed to offer an off the shelf solution for drainage projects.

Recommended for applications including subdivision inter allotment drainage through to commercial and industrial complexes.

The risers come in a range of standard sizes offering greater flexibility on site compared with cast insitu and custom made pits.

Manufactured and tested as per AS4671 to meet class D wheel loading.

USES

- Residential Drainage
- Sports fields
- Commercial and Industrial Complexes

FEATURES

- Wet cast
- Tested to Class D wheel loading
- Minimum 40mpa Concrete
- Steel reinforcement to AS4671
- Polypropylene fiber reinforcement mean strength of 650mpa
- Concrete Lifting eye's for safety

CONCRETE RISER ACCESSORIES

Jaybro supplies a wide range of accessories to pair with our riser unites. Including pits, grates and lids. If you can't find the solution you are looking for, call 1300 885 364 now! Our drainage experts can recommend a solution to fill your need. We can source and manufacture precast concrete solutions to fill your needs.

Additional Information

CODE	PR090601
U.O.M	Each
Weight	250
Dimensions	900 x 600 x 150 mm
Length	600 mm
Height	900 mm
Width	150 mm

