

# Red PVC Layflat hose, 65 mm ID / 2.5" ID. Sold in custom lengths by the metre.

## **Product Images**



### **Short Description**

65 mm ID lay flat hose. Sold by the metre - enter the number of meters required e.g. 15m = 15 to purchase. Standard length coils also available in 20m or 100m. Suitable for general discharge and transfer of water, chemicals and fluids in construction and mining applications.

### **Description**

Red Layflat Hose, 65 mm or 2.5" ID. Sold by the metre in continuous lengths up to 100 metres. Standard lengths are 20 metres and 100 metres, or Jaybro can supply a custom length of hose complete with fittings for your requirements.

Suitable for general discharge of water in construction and mining operations.

Jaybro's red layflat hose has a Safety Factor of 3:1, meaning that the burst pressure is three times the operating pressure of this hose. With a temperature range of -10 degrees Celcius to +60 degrees Celcius, it is ideal for heavy duty washdown and dewatering in mining applications and for general civil and construction operations.

Jaybro's layflat hose is constructed from abrasion and ozone resistant red PVC and can stand up to the rigors of harsh weather, prolonged exposure to full sun, and low temperature fluid transfer. When under pressure, lay flat hoses adopt a tubular appearance, but when hoses are discharged they return to a flat profile therefore allowing for easy transport and handling. Layflat hoses are easy to pack away when note in use, saving valuable storage space.

Additionally, suction hoses do not require drying time. They can be rolled up for transportation and storage immediately after use due to their rugged PVC construction.

Plus, you can personalise your hose to suit your particular project: Jaybro stocks a wide range of hose fitting and clamps including Camlock, Bauer, Travis and Strainers claw type fittings to suit your specific needs. We can fit any hosetail kit you require.

Jaybro keeps up to 95% of our product on the shelf and in stock so we can deliver to you, fast!

- 65 mm ID / 2.5" ID
- 68 mm OD
- Wall thickness 2.2 mm
- Working temperature -10 degrees Celcius +60 degrees Celcius
- Rated to working pressure of 1 bar / 150 psi
- Abrasion and ozone resistant
- Red PVC construction
- Suitable for fluid delivery or discharge
- Hose without fittings weighs 0.56kg per metre

# **Additional Information**

CODE	WU-HS-6103M
U.O.M	Linear Metre
Hose Type	Construction & mining
Material	PVC
Colour	Red
Size	65 mm I.D
Size (O.D)	68 mm
Pressure (bar)	1
Pressure (psi)	150
Min Working Temp	-10 degrees Celcius
Max Working Temp	+60 degrees Celcius
Wall Thickness (mm)	2.2

