

Red PVC Layflat hose kit, 20m x 65 mm ID / 2.5" ID fitted with camlocks

Product Images



Short Description

65 mm ID lay flat hose with camlocks. Standard length coil available in 20m. Suitable for general discharge and transfer of water, chemicals and fluids in construction and mining applications.

Description

Red Layflat Hose Kit, $20m \times 65 \text{ mm}$ or 2.5" ID with camlocks. Sold in a standard legth of 20 metres, or Jaybro can supply a custom length of hose complete with fittings for your requirements.

Suitable for general discharge of water, chemicals and fluids in agriculture, landscaping, industrial, cleaning and construction operations.

Jaybro's red layflat hose has a Safety Factor of 3:1, meaning that the burst pressure is three times the operating pressure of this hose. With a temperature range of -10 degrees Celcius to +60 degrees Celcius, it is ideal for heavy duty washdown and dewatering in mining applications and for general civil and construction operations.

Jaybro's layflat hose is constructed from abrasion and ozone resistant red PVC and can stand up to the rigors of harsh weather, prolonged exposure to full sun, and low temperature fluid transfer. When under pressure, lay flat hoses adopt a tubular appearance, but when hoses are discharged they return to a flat profile therefore allowing for easy transport and handling. Layflat hoses are easy to pack away when note in use, saving valuable storage space.

Additionally, suction hoses do not require drying time. They can be rolled up for transportation and storage immediately after use due to their rugged PVC construction.

Jaybro keeps up to 95% of our product on the shelf and in stock so we can deliver to you, fast!

- 65 mm ID / 2.5" ID
- 68 mm OD
- Wall thickness 1.5mm
- Working temperature -10 degrees Celcius to +60 degrees Celcius
- Rated to working pressure of 10 bar / 150 psi
- Abrasion and ozone resistant
- Red PVC construction
- Suitable for fluid delivery
- Fitted in-house with Camlock fittings.
- Contact us if you require different fittings such as Travis, Bauer, Strainers and claw type fittings.

Additional Information

CODE	RLHK-1101
U.O.M	Each
Hose Type	Construction & mining
Material	PVC
Colour	Red
Dimensions	65 mm x 20m
End Style	Camlock fittings
Size	65 mm I.D
Size (O.D)	68 mm
Pressure (bar)	10
Pressure (psi)	150
Min Working Temp	-10 degrees Celcius
Max Working Temp	+60 degrees Celcius
Wall Thickness (mm)	2.2

