

---

# Black rubber layflat hose kit, 20m x 250 mm ID / 10" ID fitted with Bauer fittings

## Product Images

---



## Short Description

---

250 mm ID lay flat hose with Bauer fittings. Standard length coil available in 20m. Suitable for general discharge and transfer of water, chemicals and fluids in construction and mining applications.

## Description

---

Black Layflat Hose Kit, 20m x 250 mm or 10" ID with Bauer fittings. Sold in a standard length of 20 metres, or Jaybro can supply a custom length of hose complete with fittings for your requirements.

Suitable for general discharge of water in heavy agriculture and industrial applications.

Jaybro's red layflat hose has a Safety Factor of 3:1, meaning that the burst pressure is three times the operating pressure of this hose. With a temperature range of -20 degrees Celcius to +80 degrees Celcius, it is ideal for heavy duty washdown, watering and dewatering in agriculture applications and for general industrial processes. Ideal for when water needs to be moved to considerably higher or lower elevations.

Jaybro's layflat hose is constructed from black synthetic rubber with a polyester-polyamide textile filament and can stand up to the rigors of harsh weather, prolonged exposure to full sun, and low temperature fluid transfer. When under pressure, lay flat hoses adopt a tubular appearance, but when hoses are discharged they return to a flat profile therefore allowing for easy transport and handling. Layflat hoses are easy to pack away when not in use, saving valuable storage space.

Additionally, suction hoses do not require drying time. They can be rolled up for transportation and storage immediately after use due to their rugged PVC construction.

Jaybro keeps up to 95% of our product on the shelf and in stock so we can deliver to you, fast!

- 250 mm ID / 10" ID
- 257 mm OD
- Wall thickness 3.5mm
- Working temperature -20 degrees Celcius to +80 degrees Celcius
- Rated to working pressure of 8 bar / 120 psi
- Abrasion and ozone resistant
- Black rubber construction
- Suitable for fluid delivery
- Fitted in-house with Bauer fittings.
- Contact us if you require different fittings such as Travis, Camlocks, Strainers and claw type fittings.

## Additional Information

---

CODE	HLHK-1304
U.O.M	Each
Weight	0.01
Hose Type	Water & general liquids
Material	Rubber
Colour	Black
End Style	Bauer fittings
Size	250 mm I.D
Size (O.D)	257 mm
Pressure (bar)	8
Pressure (psi)	120
Min Working Temp	-20 degrees Celcius
Max Working Temp	+80 degrees Celcius
Wall Thickness (mm)	3.5

