

# **Type E Aluminium Camlocks**

# **Product Images**





### **Short Description**

Aluminium Camlocks Type E in a range of sizes from 3/4" to 6". Choose your size from the dropdown box below. Also available in stainless steel, Brass, nyglass and polypropylene on request.

#### **Description**

Camlock fitting Type E, available in sizes from 19 mm to 150 mm. Constructed from aluminium, these camlock fittings are heavy duty and reliable. Jaybro has a wide range of hoses available, ask us about fitting camlocks to hoses in-house to create complete kit.

A camlock fitting is a hose coupling consisting of male and female parts that click together to form a watertight seal. This kind of coupling is popular because it is a simple and reliable means of connecting and disconnecting hoses quickly and without tools.

These hose couplings enable connection or disconnection of a hose in an efficient way, guaranteeing tight and secure bonds. The cams lock into place using a simple male and female mechanism - a male groove adapter and female cam. To connect and disconnect your camlock simply extend the handles on the coupler outwards and place the correct size male adapter into the female coupler. Then close the handles in one movement, which ensures an even connection and a consequently a leak proof seal. Reverse the process to disconnect the hose assembly, after first ensuring the hose is not charged (ie it has been de-pressurised).

Ensure you get the right size you need for your hose by correctly measuring your hose tail, male or female thread - ie: a 1" hose tail fits a 1" metal camlock. Camlock fittings are available in different types or configurations as follows:

- Type A: Adapter with female thread
- Type B: Coupler with male thread

- Type C: Coupler with hose tail
- Type D: Coupler with female thread
- Type E: Adapter with a hose tail
- Type F: Adapter with male thread
- Dust caps are also available, categorised as DC: dust caps for adapters and DP: dust plugs for couplers

## **Additional Information**

CODE	AL-EC-WP
U.O.M	Each

## **Product Options**

Size:	19 mm
	25 mm
	32 mm
	38 mm
	50 mm
	65 mm
	75 mm
	100 mm
	150 mm

