

Soudal Firecryl FR

Product Images





Short Description

Firecryl FR is a fire-resistant, smoke-tight, with heat load intumescent plasto-elastic sealant based on acrylic dispersion.

Always consult a fire engineer before use in a fire rated application.

Description

Features & Benefits

- Prevents the passage of fire and smoke
- Intumesces when exposed to temperatures higher than 120°C
- Can be painted over after curing
- Very easy to apply
- Permanently elastic after curing
- Colourfast and waterproof after curing
- Very good adhesion on many porous materials

Applications

- Fire-resistant and smoke-tight indoor applications.
- As part of the 'Soudal Fire Range' assortment for penetration seals and joints.
- Sealing of fire retardant joints in walls and ceiling.
- Fire-retardant filling of cracks in concrete and plasterwork.
- Applications where the sealant needs to be overpainted with water based paints and varnishes.

Additional Information

CODE	40-FS600
U.O.M	Each
Colour	Grey
Type	Fire Retardant
Suits Substrate	Aluminium, Concrete, Mortar, Plasterboard, Steel
Box Quantity	15
Brand	HB Fuller
Size	600 ml
Min Working Temp	-20 degrees Celsius
Max Working Temp	+80 degrees Celsius
Gel Time / Skin Time	Skins in 15 minutes (typical)
Shore A Hardness	25 - 35

