

Ramset Chemset Reo 502 Plus 600ml

Product Images



Short Description

Ramset Chemset Reo 502 Plus 600ml High-performance pure epoxy anchoring adhesive. A heavy-duty pure Epoxy for anchoring threaded studs and reinforcing bar into cracked & uncracked concrete.

Description

Chemset Reo 502 Plus is a heavy duty anchoring epoxy for use on cracked concrete and for seismic applications. It is a a pure epoxy formulation forming strong bonds to concrete. Prequalification to AS5216:2018 and NCC 2019; for use in cracked concrete and seismic applications. Reo502 PLUS is designed for fast, all-weather dispensing. It offers user friendly working times to maximise productivity. Reo502 PLUS is for structural reinforcing bar connections and structural anchoring applications.

Features:

- Fast, low fatigue dispensing, high performance pure epoxy
- Low viscosity
- Longer nozzle life & reduced working time pressure High Bond Strength
- Low odour
- VOC Compliant

Ideal for:

- Dry, Damp, Wet and Underwater applications
- Carbide or Core Drilled*
- Structural reinforcing bar connections in slabs, columns, beams and walls, structural anchoring applications
- Oversized Diameters* (up to 2.25 x Bar Diameter)
- *Performance of cored & oversized holes was not included in the ETAG test program and therefore is based on testing conducted at ramsetreid Concrete Structures Laboratory

Additional Information

CODE	40-REO502EF600
U.O.M	Each
Colour	Grey
Suits Substrate	Concrete, Steel, Timber
Brand	Ramset
Size	600 ml
Appearance / Composition	Epoxy
Min Working Temp	-40 degrees Celsius
Max Working Temp	+70 degrees Celsius
Gel Time / Skin Time	18 min at 25 degrees Celsius
Cure Time	6hrs at 25 degrees Celsius

