

Flextool Flexdrive Pump GP 6M

Product Images



Short Description

Flexdrive Pump 6 metres length, with heavy duty and double row oil bath bearings to ensure extended service life. This Flextool submersible general purpose pump has support springs to protect drive draft when operating over the sharp edge of excavations.

Description

Flextool Pumps are highly efficient underwater units which are operated by a variety of portable drive units powered by petrol, diesel and electric motors. General purpose use on excavation pits, construction sites, pier holes, dams, swimming pools, trenches and more. The newly improved FP212G-6 flexible shaft driven pump sets the benchmark for performance and durability. Heavy duty and double row oil bath bearings ensure extended service life, and the Flexshaft support springs protect drive draft when operating over the sharp edge of excavations, pits, dams, etc.

Features:

- Corrosion resistant stainless steel spindle
- Seven oil seals for superior bearing protection
- Quick action cam lock hose fittings
- Heavy duty and double row bearings
- Oil bath lubrication
- Lifting eyelets
- Flexshaft length: available in 6m
- Operating weight: 26kg
- Hardened steel wear plates
- Heavy duty choke resistant stainless steel spindle
- 28mm solids pumping capacity

Applications:

- Excavation pits
- Construction sites
- Pier holes
- Dams
- Swimming pools
- Trenches

The Flextool Promise:

If the unexpected happens and something goes wrong with your Flextool equipment within the first 12 months of purchase, Flextool will arrange a loan machine for 2 days, free of charge, so you can get the job done. If a Flextool product breaks down on site, get in touch with Flextool customer service for assistance with arranging a loan machine through your local hire partner.

Additional Information

CODE	40-FT201801-UNIT
U.O.M	Each
Brand	Flextool
Colour	Black/Yellow
Length	6 m

