

Sika Primer 3N 1L for Sikaflex Sealants

Product Images



Short Description

Sika Primer-3 N is a solvent-based, one-part primer and adhesion promoter for porous substrates and metals. It is easy to apply, water repellent, isocyanate free and has a short flash-off time.

Sika 3N Primer is ideal for use with concrete, masonry, wood, metal and plaster.

Description

Sika Primer-3 N is a solvent-based, one-part primer and adhesion promoter for porous substrates and metals. It is easy to apply, water repellent, isocyanate free and has a short flash-off time. Sika 3N Primer is ideal for use with concrete, masonry, wood, metal and plaster.

Features:

- Promotes adhesion to clean, sound and dry concrete and masonry
- Also suitable for wood, metal and plaster
- Fast drying
- One part - no mixing required
- Dries in as little as 30 minutes

Ideal for:

- Use prior to bonding or sealing with Sikaflex products

APPLICATION

Surface Preparation:

The key to good adhesion with Sikaflex sealants is surface preparation. Specifically, all surfaces must be dry and free of dirt, grease, form release agent, loose mortar, laitance and any foreign matter. If the joint contains old sealant, it must be removed and the substrate cleaned by mechanical means. Can be used on damp substrates with maximum substrate moisture content of 8%.

Placement:

Apply primer at minimum substrate temperatures of 10 degrees Celsius and rising. Surface must be frost-free. Drying time will be minimum 30 minutes, maximum 8 hours.

Reseal container tightly after use. Discard any primer that has gelled, become cloudy or separated. Important: Do not apply at temperatures below 10 or above 30 degrees Celsius.

Storage:

Store in sealed container in a cool dry place for up to 12 months.

Yield:

Covers approximately 5 m²/L

Additional Information

CODE	40-122239
U.O.M	Each
Colour	Clear
Brand	Sika
Appearance / Composition	Liquid
Cure Time	Dries in 30 min - 8 hrs (typical)

