

Sleeve Anchors for Masonry and Concrete

Product Images





Short Description

Zinc sleeve Anchors Bolts. A torque controlled expansion anchor for medium-duty civil and construction applications. Precision stamped tubular expansion sleeve anchors with a yellow zinc coat finish. Commonly used to fasten timber and steel fixtures to concrete and masonry substrates. Often referred to as Dyna Bolts.

Description

Hex Nut Zinc Yellow Passivated Sleeve Anchor

The Sleeve Anchor is a pre-assembled Carbon Steel single unit sleeve anchor. The Sleeve Anchor diameter is the same as that for the hole which eliminates layout or hole spotting. Hex nut head style anchors consist of a threaded plow bolt which has a cone shape at the bottom end.

Features

- Precision stamped tubular expansion sleeve
- Can be used in concrete, block, brick, and stone.

| Part No. | Minimum Embedment Depth (mm) | Hole Diameter (mm) | Maximum Fixture Thickness (mm) | Socket Size (mm) |
|----------------|------------------------------|--------------------|--------------------------------|------------------|
| 40-HS6520-PWR | 18 | 6.5 | 2 | 8 |
| 40-HS6525-PWR | 20 | 6.5 | 5 | 8 |
| 40-HS6535-PWR | 30 | 6.5 | 5 | 8 |
| 40-HS6555-PWR | 30 | 6.5 | 25 | 8 |
| 40-HS6575-PWR | 30 | 6.5 | 45 | 8 |
| 40-HS0840-PWR | 35 | 8 | 5 | 10 |
| 40-HS0865-PWR | 35 | 8 | 30 | 10 |
| 40-HS0885-PWR | 35 | 8 | 50 | 10 |
| 40-HS1040-PWR | 34 | 10 | 6 | 13 |
| 40-HS1050-PWR | 40 | 10 | 10 | 13 |
| 40-HS1060-PWR | 40 | 10 | 20 | 13 |
| 40-HS1075-PWR | 40 | 10 | 35 | 13 |
| 40-HS10100-PWR | 40 | 10 | 55 | 13 |
| 40-HS10120-PWR | 40 | 10 | 80 | 13 |
| 40-HS1260-PWR | 50 | 12 | 10 | 15 |
| 40-HS1275-PWR | 50 | 12 | 25 | 15 |
| 40-HS12100-PWR | 50 | 12 | 50 | 15 |
| 40-HS12130-PWR | 50 | 12 | 80 | 15 |
| 40-HS1665-PWR | 55 | 16 | 10 | 18 |
| 40-HS16110-PWR | 55 | 16 | 55 | 18 |
| 40-HS16145-PWR | 55 | 16 | 90 | 18 |
| 40-HS2075-PWR | 60 | 20 | 15 | 24 |
| 40-HS20105-PWR | 60 | 20 | 45 | 24 |

| Part No. | Minimum Embedment Depth (mm) | Hole Diameter (mm) | Maximum Fixture Thickness (mm) | Socket Size (mm) |
|----------------|------------------------------|--------------------|--------------------------------|------------------|
| 40-HS20150-PWR | 60 | 20 | 90 | 24 |

Additional Information

| | |
|-----------------|--------------------------|
| CODE | 40-HS-WP |
| U.O.M | Each |
| Suits Substrate | Brick, Concrete, Masonry |
| Finish | Zinc |
| Material | Metal |

Product Options

| | |
|-------------|-------------|
| Dimensions: | 6.5 x 55 mm |
| | 6.5 x 35 mm |
| | 8 x 40 mm |
| | 8 x 65 mm |
| | 8 x 85 mm |
| | 10 x 75 mm |
| | 10 x 60 mm |
| | 10 x 50 mm |
| | 10 x 40 mm |
| | 10 x 120 mm |
| | 10 x 100 mm |
| | 12 x 100 mm |
| | 12 x 130 mm |
| | 12 x 60 mm |
| | 12 x 75 mm |
| | 16 x 110 mm |
| | 16 x 145 mm |
| | 16 x 65 mm |
| | 20 x 105 mm |
| | 20 x 150 mm |
| | 20 x 75 mm |

