

Speed Hump Section 250 x 350 x 50mm Black

Product Images





Short Description

Speed hump section measuring 250 mm x 350 mm. Order with **yellow speed hump sections** and **black end caps** to create the desired width speed hump for your road or driveway.

Description

- Cost effective and durable solution for control of speed
- Made from compression moulded 80% recycled rubber and 20% virgin rubber
- 2 x bolts and plugs included with each section and each end cap
- Complies with Australian Standard AS2890.1:2004 (Type 2)

Specifications

- Each piece measures 250 x 350 x 50 mm
- Fitting Holes: Middle: 2 Holes x 12 mm diameter, End Cap: 2 Holes x 12 mm diameter
- Weight: 4kg
- Bearing Capacity : 20T
- Reflector: 4 pieces supplied with each cats-eye hump section only
- Tensile Strength: 6 MPa
- Elongation at break: 200%
- Hardness: 85A
- Impact elasticity: 37%
- Abrasion Performance: 0.28 cm³ / 1.61 km

Type 2 Speed Hump:

These speed hump sections comply with Australian Standard AS2890.1:2004 Parking Facilities, and are suitable as a Type 2 road hump. This means that they meet the design criteria for height, cross section, markings and ramp angles. The hump is 50mm high which conforms to the standard specification "must be between 25mm and 75mm". The cross section is flat on top not rounded, ensuring it meets the standard. Also, the speed hump sections have the required ramp angle of 2:1, and when installed in an alternating black/yellow pattern, they provide the appropriate 250mm wide striped markings.

Additional Information

CODE	SWSH5-SECB
U.O.M	Each
Height	50 mm

