
Pro-3G Davit 2 Piece c/w Male Bracket, 2800mm

Product Images



Short Description

Davit - 2.2m 2 piece c/w Quick Release Double Sided Universal Male Interface Bracket. For use with corresponding bases, winches and other accessories from the Pro-3 Range.

Description

The Pro-3 Davit is a lightweight aluminium modular unit that is easy to set up by just one person. With a built in fall and davit overload indicator, it is rated to 18kN.

The Pro-3 davit system is a modular design allowing the user to create a davit setup for their individual requirements. With a range of brackets, winches and bases available, the Pro 3 Series is an ideal davit for confined space entry with a 1.9 - 2.8m davit allowing offset of 0.5 to 0.7 metres.

Features:

- 4 piece construction for ease of transport and storage
- Modular in design
- No tools required for set up
- Lightweight material graded 6061-T6 Aluminum
- Powdercoated safety orange to increase visibility around a workplace
- Modular in construction with no one component heavier than 10kg
- Easy to store and can be transported by 1 person
- Built in fall and davit overload indicator
- Multi-off set mast with a variable reach from 0.5m to 0.7m
- No special tools required for assembly or disassembly
- Can be setup for use with both man-rated and material-rated applications to a max WLL of 140kg - (Material Rating Only)
- Suits both fixed and portable davit bases with a mast rotation of 360 degrees
- Rated secondary anchor point on vertical mast for connection by the winch operator or standby person
- Quick release winch interface brackets to suit all BTS winches and other reputable winch brands in the market
- Complies with product design, manufacturing and testing requirements of AS/NZS1891.4, AS/NZS 5532-2013 & CE EN795
- BTS-Klick pin-less technology adjustment
- Compatible with portable and permanent davit bases

Specifications:

- Ultimate Strength Rating: 18 kN
- Capacity (Rescue): Max. 2 workers weighing not more than 136 kg each.*
- Capacity (Fall Arrest): Max. 1 worker weighing not more than 136 kg.*
- Allowable MAF Rating for SRL's: 4kN
- * Capacities quoted when used in conjunction with a man rated winch

CODE	33-30108
U.O.M	Each
Brand	BTS
Height	1900 - 2800mm



Additional Information