

# Max Frank Stremaform Formwork Elements for Working Joints

## Product Images





## Short Description

---

Stremaform formwork elements divide large structural components into individual concreting sections. The prefabricated elements are used as permanent formwork in floor slabs, ceilings and walls.

## Description

---

Max Frank Stremaform® flat is used for medium-sized structural components, installed between the upper and lower reinforcement layers. Stremaform® in the concrete gives a rough surface that satisfies the requirements of an indented joint according to DIN 1045-1 and/or Eurocode 2 and does not need scabbling. A metal water stop or a PVC/rubber waterbar support cage can be integrated in our factory if required.

Delivery is made precisely in accordance with your layout specifications. Stremaform® formwork elements are used as lost formwork in floor slabs, ceilings and walls. The expanded metal that is welded between the bars of a specially designed reinforcing steel mesh gives rise to a rough surface. The reinforcement can be continued without a break into the second concrete pour. Stremaform is suited for all types of working joints.

### Features and Benefits

- Site drawings are quickly transformed into factory produced elements
- The formwork lies between the continuous reinforcement layers so that there is no need to interrupt the reinforcement
- Elements manufactured to your specifications
- No stripping or reworking necessary
- Available with or without metal waterstops, or PVC/rubber water bar cages
- Full range of accessories available including spacers with fibre-reinforced concrete rail, support anchors, upright elements, box out, shutters, and kickers for use between base slab/wall and wall/roof slab

## Variations Available

### Stremaform sheet material

- Formwork elements for installation widths of 500 mm in horizontal slabs and 300 mm in walls
- The element is supplied as an exact fit and is installed between the reinforcement layers
- A metal water stop or a PVC/rubber waterbar support cage can be installed if required

**Stremaform strong flat material**

- Formwork elements for any slab and wall thickness
- Suited for very thick components due to vertical stiffening
- The element is supplied as an exact fit and is installed between the reinforcement layers

**Stremaform with Indented Joint**

- All Stremaform® elements can be supplied with single or multiple indented joints. The standard indented joint satisfies the requirements of Eurocode 2.

**Stremaform formwork element with concrete spacer bar, double-sided**

- Formwork element with integrated extruded fibre concrete rail for shuttering slabs and walls.  
**Please contact Jaybro for a quote on your specific project.**

**Additional Information**

CODE	40-PV3000-WP
Suits Substrate	Concrete
Brand	Max Frank

**Product Options**

Length:	2400 mm
Width:	100 mm
	200 mm
	250 mm
	350 mm
	400 mm
	450 mm
	500 mm
	600 mm
	1000mm

