

# Max Frank Stremaform Formwork Elements for Working Joints

## Product Images





## Short Description

---

Stremaform formwork elements divide large structural components into individual concreting sections. The prefabricated elements are used as permanent formwork in floor slabs, ceilings and walls.

## Description

---

Max Frank Stremaform® flat is used for medium-sized structural components, installed between the upper and lower reinforcement layers. Stremaform® in the concrete gives a rough surface that satisfies the requirements of an indented joint according to DIN 1045-1 and/or Eurocode 2 and does not need scabbling. A metal water stop or a PVC/rubber waterbar support cage can be integrated in our factory if required.

Delivery is made precisely in accordance with your layout specifications. Stremaform® formwork elements are used as lost formwork in floor slabs, ceilings and walls. The expanded metal that is welded between the bars of a specially designed reinforcing steel mesh gives rise to a rough surface. The reinforcement can be continued without a break into the second concrete pour. Stremaform is suited for all types of working joints.

### Features and Benefits

- Site drawings are quickly transformed into factory produced elements
- The formwork lies between the continuous reinforcement layers so that there is no need to interrupt the reinforcement
- Elements manufactured to your specifications
- No stripping or reworking necessary
- Available with or without metal waterstops, or PVC/rubber water bar cages
- Full range of accessories available including spacers with fibre-reinforced concrete rail, support anchors, upright elements, box out, shutters, and kickers for use between base slab/wall and wall/roof slab

## Variations Available

### Stremaform sheet material

- Formwork elements for installation widths of 500 mm in horizontal slabs and 300 mm in walls
- The element is supplied as an exact fit and is installed between the reinforcement layers
- A metal water stop or a PVC/rubber waterbar support cage can be installed if required

### Stremaform strong flat material

- Formwork elements for any slab and wall thickness
- Suited for very thick components due to vertical stiffening
- The element is supplied as an exact fit and is installed between the reinforcement layers

### Stremaform with Indented Joint

- All Stremaform® elements can be supplied with single or multiple indented joints. The standard indented joint satisfies the requirements of Eurocode 2.

### Stremaform formwork element with concrete spacer bar, double-sided

- Formwork element with integrated extruded fibre concrete rail for shuttering slabs and walls.  
**Please contact Jaybro for a quote on your specific project.**

## Additional Information

---

|                 |              |
|-----------------|--------------|
| CODE            | 40-PV3000-WP |
| Suits Substrate | Concrete     |
| Brand           | Max Frank    |

## Product Options

---

|         |         |
|---------|---------|
| Length: | 2400 mm |
| Width:  | 100 mm  |
|         | 200 mm  |
|         | 250 mm  |
|         | 350 mm  |
|         | 400 mm  |
|         | 450 mm  |
|         | 500 mm  |
|         | 600 mm  |
|         | 1000mm  |

