

600 x 1250mm Class B Gas and airtight covers Infill Cover

Product Images



Short Description

600 x 1200mm Class B Ductile Iron Infill Cover and Frame

Description

Commonly used for junction pits and onsite detention tanks, Jaybro's range of concrete infill ductile iron access covers are designed to allow easy access for maintenance crews. The heavy duty frame is designed to be cast into a concrete slab in the tank or above the pit, and the cover is filled with concrete, making the pit or tank sealed against gas, air and water ingress. Manufactured and tested to meet Australian Standard AS3996.2006 Access Covers and Grates, this range of covers is available rated to Class D or Class B - hoose from the options below.

Class B loading is typically for areas including footways and light tractor paths that are accessible to vehicles (excluding commercial vehicles) or livestock (light duty). Class B classified products have a nominal wheel loading of 2670 kg, a serviceability design load of 53kN and an ultimated limit state design load of 80kN.

Class D loading is typically for carriageways of roads and areas open to commercial vehicles (heavy duty). Class D classified products have a nominal wheel loading of 8000 kg, a serviceability design load of 140kN and an ultimate limit state design load of 210kN.

Choose from a range of standard sizes including:

- 450 x 450 mm
- 600 x 600 mm
- 600 x 900 mm
- 900 x 900 mm
- 1200 x 1200 mm

Additional Information

CODE	INDICF0612B
U.O.M	Each
Weight	109
Dimensions	1200 x 600 mm
Туре	Class B
Swatch	no_selection

